



# 上海阜风机电设备有限公司

咨询:15221392169

参数价格表 2017-2-15

(配置IP55三相电机)

型号 2GB (3AC)	单叶轮	马达参数				最大	额定	额定	噪音 noises dB(A)	重量 Weight Kg	
	双叶轮	频率	功率	额定电压		排吸流量	真空压力	压缩压力			
	single	frequency	power	voltage		current	rated Vacuum	rated compress			
	double	HZ	KW	V		A	m3/h	mbar			
2GB 210 H16	单	50	0.4	200-240 Δ	345-415Y	2.6 Δ / 1.5Y	80	-120	130	53	10
		60	0.5	220-275 Δ	380-480Y	2.6 Δ / 1.5Y	98	-150	160	56	
2GB 220 H26	双	50	0.7	200-240 Δ	345-415Y	3.8 Δ / 2.2Y	85	-210	240	55	15
		60	0.83	220-275 Δ	380-480Y	3.75 Δ / 2.15Y	102	-250	250	61	
2GB 230 H16	单	50	0.4	200-240 Δ	345-415Y	2.6 Δ / 1.5Y	105	-120	130	54	11
		60	0.5	220-275 Δ	380-480Y	2.6 Δ / 1.5Y	120	-150	160	57	
2GB 230 H26	单	50	0.7	200-240 Δ	345-415Y	3.8 Δ / 2.2Y	105	-120	140	54	12
		60	0.83	220-275 Δ	380-480Y	3.8 Δ / 2.2Y	120	-160	180	57	
2GB 310 H06	单	50	0.55	200-240 Δ	345-415Y	2.8 Δ / 1.6Y	100	-110	120	55	11
		60	0.63	220-275 Δ	380-480Y	3.0 Δ / 1.7Y	120	-110	120	57	
2GB 310 H16	单	50	0.7	200-240 Δ	345-415Y	3.8 Δ / 2.2Y	100	-150	150	55	12
		60	0.83	220-275 Δ	380-480Y	3.8 Δ / 2.2Y	120	-150	140	57	
2GB 320 H26	双	50	0.85	200-240 Δ	345-415Y	4.2 Δ / 2.4Y	110	-200	230	58	17
		60	0.95	220-275 Δ	380-480Y	4.0 Δ / 2.3Y	130	-240	240	60	
2GB 320 H36	双	50	1.3	200-240 Δ	345-415Y	5.7 Δ / 3.3Y	110	-280	290	58	18
		60	1.5	220-275 Δ	380-480Y	6.0 Δ / 3.5Y	130	-300	400	60	
2GB 330 H06	单	50	0.55	200-240 Δ	345-415Y	2.8 Δ / 1.6Y	140	-60	60	56	12
		60	0.63	220-275 Δ	380-480Y	3.0 Δ / 1.7Y	165	-50	50	58	
2GB 330 H16	单	50	0.7	200-240 Δ	345-415Y	3.8 Δ / 2.2Y	140	-100	100	56	13
		60	0.83	220-275 Δ	380-480Y	3.8 Δ / 2.2Y	165	-115	100	58	
2GB 410 H06	单	50	0.7	200-240 Δ	345-415Y	3.8 Δ / 2.2Y	145	-120	120	63	15
		60	0.83	220-275 Δ	380-480Y	3.75 Δ / 2.15Y	175	-140	140	64	
2GB 410 H16	单	50	0.85	200-240 Δ	345-415Y	4.0 Δ / 2.3Y	145	-160	160	63	17
		60	0.95	220-275 Δ	380-480Y	3.85 Δ / 2.25Y	175	-160	160	64	
2GB 410 H26	单	50	1.3	200-240 Δ	345-415Y	5.7 Δ / 3.3Y	145	-170	200	63	18
		60	1.5	220-275 Δ	380-480Y	6.0 Δ / 3.5Y	175	-210	220	64	

型号 2GB (3AC)	单叶轮	马达参数		最大		额定	额定	噪音 noises dB(A)	重量 Weight Kg		
	双叶轮	频率	功率	额定电压		排吸流量	真空压力			压缩压力	
	single	frequency	power	voltage		current	Max airflow			rated Vacuum	rated compress
	double	HZ	KW	V		A	m3/h			mbar	mbar
2GB 420 H36	双	50	1.6	200-240 Δ	345-415Y	7.5 Δ / 4.3Y	150	-280	280	66	25
		60	2.05	220-275 Δ	380-480Y	7.6 Δ / 4.4Y	180	-320	310	69	
2GB 420 H46	双	50	2.2	200-240 Δ	345-415Y	9.7 Δ / 5.6Y	150	-330	420	66	27
		60	2.55	220-275 Δ	380-480Y	10 Δ / 5.8Y	180	-350	440	69	
2GB 430 H06	单	50	0.7	200-240 Δ	345-415Y	3.8 Δ / 2.2Y	180	-70	70	64	14
		60	0.83	220-275 Δ	380-480Y	3.8 Δ / 2.2Y	210	-50	50	65	
2GB 430 H16	单	50	0.85	200-240 Δ	345-415Y	4.2 Δ / 2.4Y	180	-110	100	64	17
		60	0.95	220-275 Δ	380-480Y	4.0 Δ / 2.3Y	210	-90	70	65	
2GB 430 H26	单	50	1.3	200-240 Δ	345-415Y	6.6 Δ / 3.8Y	180	-180	180	64	18
		60	1.5	220-275 Δ	380-480Y	6.9 Δ / 4.0Y	210	-180	170	65	
2GB 490 H16	单	50	0.7	200-240 Δ	345-415Y	2.5 Δ / 1.4Y	140	-120	120	63	14
		60	0.83	220-275 Δ	380-480Y	2.7 Δ / 1.6Y	175	-140	140	64	
2GB 510 H06	单	50	0.85	200-240 Δ	345-415Y	4.2 Δ / 2.3Y	210	-110	100	64	20
		60	0.95	220-275 Δ	380-480Y	4.0 Δ / 2.3Y	255	-80	70	70	
2GB 510 H16	单	50	1.3	200-240 Δ	345-415Y	6.6 Δ / 3.8Y	210	-170	170	64	22
		60	1.5	220-275 Δ	380-480Y	6.9 Δ / 4.0Y	255	-150	140	70	
2GB 510 H26	单	50	1.6	200-240 Δ	345-415Y	7.5 Δ / 4.3Y	210	-200	190	64	23
		60	2.05	220-275 Δ	380-480Y	7.6 Δ / 4.4Y	255	-220	210	70	
2GB 510 H36	单	50	2.2	200-240 Δ	345-415Y	9.7 Δ / 5.6Y	210	-220	270	64	26
		60	2.55	220-275 Δ	380-480Y	10.3 Δ / 6.0Y	255	-260	290	70	
2GB 520 H36	双	50	2.2	200-240 Δ	345-415Y	9.7 Δ / 5.6Y	230	-290	360	72	35
		60	2.55	220-275 Δ	380-480Y	10.3 Δ / 6.0Y	275	-350	330	74	
2GB 520 H46	双	50	3	200-240 Δ	345-415Y	12.5 Δ / 7.2Y	230	-340	410	72	39
		60	3.45	220-275 Δ	380-480Y	12.6 Δ / 7.3Y	275	-380	360	74	
2GB 520 H57	双	50	4	345-415 Δ	600-720Y	10 Δ / 5.8Y	230	-390	490	72	44
		60	4.6	380-480 Δ	660-720Y	9.9 Δ / 5.71Y	275	-410	480	74	
2GB 530 H06	单	50	0.85	345-415 Δ	600-720Y	4.0 Δ / 2.3Y	270	-40	40	65	21
		60	0.95	380-480 Δ	660-720Y	4.2 Δ / 2.4Y	330	-40	40	71	

型号 2GB (3AC)	单叶轮	马达参数				最大	额定	额定	噪音 noises dB(A)	重量 Weight Kg	
	双叶轮	频率	功率	额定电压		排吸流量	真空压力	压缩压力			
	single	frequency	power	voltage		current	Max airflow	rated Vacuum			rated compress
	double	HZ	KW	V		A	m3/h	mbar			mbar
2GB 530 H16	单	50	1.3	345-415 Δ	600-720Y	6.6 Δ /3.8Y	270	-120	110	65	23
		60	1.5	380-480 Δ	660-720Y	6.9 Δ /4.0Y	330	-90	80	71	
2GB 530 H26	单	50	1.6	345-415 Δ	600-720Y	7.5 Δ /4.3Y	270	-160	150	65	24
		60	2.05	380-480 Δ	660-720Y	7.6 Δ /4.4Y	330	-160	150	71	
2GB 530 H36	单	50	2.2	345-415 Δ	600-720Y	9.7 Δ /5.6Y	270	-220	230	65	26
		60	2.55	380-480 Δ	660-720Y	10.3 Δ /6Y	330	-260	250	71	
2GB 5310 H07	三	50	3	345-415 Δ	600-720Y	9.7 Δ /5.3Y	200	-430	470	71	51
		60	3.45	380-480 Δ	660-720Y	10 Δ /5.5Y	260	-450	510	73	
2GB 5310 H17	三	50	4	345-415 Δ	600-720Y	10 Δ /5.8Y	220	-450	500	73	53
		60	4.6	380-480 Δ	660-720Y	10.3 Δ /5.9Y	280	-470	540	75	
2GB 590 H26	单	50	0.85	345-415 Δ	600-720Y	4.0 Δ /2.3Y	210	-130	150	64	23
		60	0.95	380-480 Δ	660-720Y	4.2 Δ /2.4Y	255	-180	210	71	
2GB 610 H06	单	50	1.6	200-240 Δ	345-415Y	8.5 Δ /4.9Y	265	-170	180	67	24
		60	2.05	220-275 Δ	380-480Y	8.8 Δ /5.5Y	315	-180	190	70	
2GB 610 H16	单	50	2.2	200-240 Δ	345-415Y	9.7 Δ /5.6Y	265	-235	220	67	27
		60	2.55	220-275 Δ	380-480Y	10.3 Δ /6.0Y	315	-245	230	70	
2GB 610 H26	单	50	3	200-240 Δ	345-415Y	12.5 Δ /7.2Y	270	-280	280	69	32
		60	3.45	220-275 Δ	380-480Y	12.6 Δ /7.3Y	315	-260	270	72	
2GB 630 H06	单	50	1.6	200-240 Δ	345-415Y	8.5 Δ /4.9Y	345	-125	125	70	36
		60	2.05	220-275 Δ	380-480Y	8.8 Δ /5.1Y	415	-105	130	73	
2GB 630 H16	单	50	2.2	200-240 Δ	345-415Y	9.7 Δ /5.6Y	345	-200	195	70	29
		60	2.55	220-275 Δ	380-480Y	10.3 Δ /6.0Y	415	-170	195	73	
2GB 630 H26	单	50	3	200-240 Δ	345-415Y	12.5 Δ /7.2Y	345	-240	220	70	35
		60	3.45	220-275 Δ	380-480Y	12.6 Δ /7.3Y	415	-210	220	73	
2GB 710 H16	单	50	2.2	200-240 Δ	345-415Y	9.7 Δ /5.6Y	318	-190	190	69	31
		60	2.55	220-275 Δ	380-480Y	10.3 Δ /6.0Y	376	-190	190	72	
2GB 710 H26	单	50	3	200-240 Δ	345-415Y	12.5 Δ /7.2Y	318	-260	270	69	36
		60	3.45	220-275 Δ	380-480Y	12.5 Δ /7.3Y	376	-240	230	72	

型号 2GB (3AC)	单叶轮	马达参数		额定电压		额定电流	最大	额定	额定	噪音 noises dB(A)	重量 Weight Kg
	双叶轮	频率	功率	额定电压		额定电流	排吸流量	真空压力	压缩压力		
	single	frequency	power	voltage		current	Max airflow	rated Vacuum	rated compress		
	double	HZ	KW	V		A	m3/h	mbar	mbar		
2GB 710 H37	单	50	4	345-415 Δ	600-720Y	9.0 Δ / 5.2Y	318	-290	360	69	40
		60	4.6	380-480 Δ	660-720Y	9.0 Δ / 5.2Y	376	-320	310	72	
2GB 710 H47	单	50	4.3	345-415 Δ	600-720Y	9.5 Δ / 5.5Y	318	-295	335	69	43
		60	4.8	380-480 Δ	660-720Y	9.5 Δ / 5.5Y	376	-335	335	72	
2GB 720 H16	双	50	2.2	200-240 Δ	345-415Y	9.7 Δ / 5.6Y	320	-220	210	73	45
		60	2.55	220-275 Δ	380-480Y	10.3 Δ / 6.0Y	380	-170	150	76	
2GB 720 H26	双	50	3	200-240 Δ	345-415Y	12.5 Δ / 7.2Y	320	-280	260	73	49
		60	3.45	220-275 Δ	380-480Y	12.6 Δ / 7.3Y	380	-230	200	76	
2GB 720 H27	双	50	4	345-415 Δ	600-720Y	9.0 Δ / 5.2Y	320	-355	375	73	53
		60	4.6	380-480 Δ	660-720Y	9.4 Δ / 5.2Y	385	-345	315	76	
2GB 720 H37	双	50	4.3	34-415 Δ	600-720Y	10 Δ / 5.2Y	320	-360	380	73	56
		60	4.8	380-480 Δ	660-720Y	10.4 Δ / 6.0Y	380	-350	320	76	
2GB 720 H47	双	50	5.5	345-415 Δ	600-720Y	13.3 Δ / 7.7Y	320	-440	500	73	70
		60	6.3	380-480 Δ	660-720Y	13.3 Δ / 7.7Y	380	-440	500	76	
2GB 720 H57	双	50	7.5	345-415 Δ	600-720Y	16.7 Δ / 9.6Y	320	-440	570	73	74
		60	8.6	380-480 Δ	660-720Y	17.3 Δ / 10.0Y	380	-460	660	76	
2GB 730 H16	单	50	2.2	200-240 Δ	345-415Y	9.7 Δ / 5.6Y	420	-180	170	70	32
		60	2.55	220-275 Δ	380-480Y	10.3 Δ / 6.0Y	500	-160	150	73	
2GB 730 H26	单	50	3	200-240 Δ	345-415Y	12.5 Δ / 7.2Y	420	-220	200	70	37
		60	3.45	220-275 Δ	380-480Y	12.6 Δ / 7.3Y	500	-200	170	73	
2GB 730 H37	单	50	4	345-415 Δ	600-720Y	9.0 Δ / 5.2Y	420	-260	280	70	43
		60	4.6	380-480 Δ	660-720Y	9.0 Δ / 5.2Y	500	-260	260	73	
2GB 730 H37	单	50	4.3	345-415 Δ	600-720Y	9.2 Δ / 5.5Y	420	-260	280	70	43
		60	4.8	380-480 Δ	660-720Y	9.2 Δ / 5.5Y	500	-260	260	73	
2GB 740 H37	双	50	4	345-415 Δ	600-720Y	9.0 Δ / 5.2Y	500	-150	140	74	54
		60	4.6	380-480 Δ	660-720Y	9.0 Δ / 5.2Y	600	-100	90	78	

型号 2GB (3AC)	单叶轮	马达参数		最大		额定	额定	噪音 noises dB(A)	重量 Weight Kg		
	双叶轮	频率	功率	额定电压		排吸流量	真空压力			压缩压力	
	single	frequency	power	voltage		current	Max airflow			rated Vacuum	rated compress
	double	HZ	KW	V		A	m3/h			mbar	mbar
2GB 740 H47	双	50	5.5	345-415 Δ	600-720Y	13.3 Δ / 7.7Y	500	-240	260	74	69
		60	6.3	380-480 Δ	660-720Y	13.3 Δ / 7.7Y	600	-210	200	78	
2GB 740 H57	双	50	7.5	345-415 Δ	600-720Y	16.7 Δ / 9.6Y	500	-240	320	74	75
		60	8.6	380-480 Δ	660-720Y	17.3 Δ / 10.0Y	600	-270	300	78	
2GB 790 H26	单	50	2.2	200-240 Δ	345-415Y	12.5 Δ / 7.2Y	320	-160	200	69	36
		60	3.45	220-275 Δ	380-480Y	12.6 Δ / 7.3Y	370	-240	250	72	
2GB 7310 H07	三	50	4.3	345-415 Δ	600-720Y	10 Δ / 5.2Y	300	-410	430	75	66
		60	4.8	380-480 Δ	660-720Y	10.4 Δ / 6.0Y	360	-400	370	78	
2GB 750-30 H07	单	50	3	200-240 Δ	345-415Y	12.5 Δ / 7.2Y	540	-180	170	81	47
		60	3.45	220-275 Δ	380-480Y	12.6 Δ / 7.3Y	635	-120	130	83	
2GB 750-30 H17	单	50	4.3	345-415 Δ	600-720Y	11 Δ / 6.5Y	540	-210	200	83	50
		60	4.8	380-480 Δ	660-720Y	12.5 Δ / 7.2Y	635	-150	140	85	
2GB 750-30 H27	单(1AC)	50	4.3	200-240 Δ	345-415Y	15 Δ / 8.5Y	540	-210	200	83	50
		60	4.8	220-275 Δ	380-480Y	15.5 Δ / 9.0Y	635	-150	140	85	
2GB 810 H07	单	50	4.3	345-415 Δ	600-720Y	9.5 Δ / 5.5Y	530	-200	200	70	51
		60	4.6	380-480 Δ	660-720Y	9.5 Δ / 5.5Y	620	-160	160	74	
2GB 810 H17	单	50	5.5	345-415 Δ	600-720Y	12.9 Δ / 7.4Y	530	-300	320	80	62
		60	6.3	380-480 Δ	660-720Y	12.9 Δ / 7.45Y	620	-320	340	82	
2GB 810 H27	单	50	7.5	345-415 Δ	600-720Y	16.7 Δ / 9.6Y	530	-320	380	80	65
		60	8.6	380-480 Δ	660-720Y	17.3 Δ / 10.0Y	620	-350	400	82	
2GB 820 H17	双	50	5.5	345-415 Δ	600-720Y	13.3 Δ / 7.7Y	520	-240	240	74	83
		60	6.3	380-480 Δ	660-720Y	13.3 Δ / 7.7Y	620	-170	160	78	
2GB 820 H27	双	50	7.5	345-415 Δ	600-720Y	16.7 Δ / 9.6Y	520	-400	400	74	88
		60	8.6	380-480 Δ	660-720Y	17.3 Δ / 10.0Y	620	-360	330	78	
2GB 820 H37	双	50	11	345-415 Δ	600-720Y	28.0 Δ / 16.2Y	520	-430	660	74	104
		60	12.6	380-480 Δ	660-720Y	29.0 Δ / 16.7Y	620	-460	600	78	
2GB 820 H47	双	50	15	345-415 Δ	600-720Y	32.5 Δ / 18.8Y	520	-460	670	74	120
		60	17.3	380-480 Δ	660-720Y	34.5 Δ / 19.9Y	620	-490	750	78	

型号 2GB (3AC)	单叶轮	马达参数		最大		额定	额定	噪音 noises dB(A)	重量 Weight Kg		
	双叶轮	频率	功率	额定电压		排吸流量	真空压力			压缩压力	
	single	frequency	power	voltage		current	Max airflow			rated Vacuum	rated compress
	double	HZ	KW	V		A	m3/h			mbar	mbar
2GB 830 H07	单	50	4.3	345-415Δ	600-720Y	9.5Δ/5.5Y	700	-150	140	70	57
		60	4.8	380-480Δ	660-720Y	9.5Δ/5.5Y	840	-90	90	74	
2GB 830 H17	单	50	5.5	345-415Δ	600-720Y	12.9Δ/7.4Y	700	-200	180	70	66
		60	6.3	380-480Δ	660-720Y	12.9Δ/7.45Y	840	-180	180	74	
2GB 830 H27	单	50	7.5	345-415Δ	600-720Y	16.7Δ/9.6Y	700	-270	260	70	69
		60	8.6	380-480Δ	660-720Y	17.3Δ/10.0Y	840	-270	260	74	
2GB 840 H17	双	50	5.5	345-415Δ	600-720Y	16Δ/9Y	870	180	150	72	83
		60	6.3	380-480Δ	660-720Y	16.5Δ/9.5Y	1000	-130	100	75	
2GB 840 H27	双	50	7.5	345-415Δ	600-720Y	16.7Δ/9.6Y	900	-200	180	74	91
		60	8.6	380-480Δ	660-720Y	17.3Δ/10.0Y	1050	-150	120	78	
2GB 840 H37	双	50	11	345-415Δ	600-720Y	28.0Δ/16.2Y	900	-280	370	74	110
		60	12.6	380-480Δ	660-720Y	29.0Δ/16.7Y	1050	-310	350	78	
2GB 840 H47	双	50	15	345-415Δ	600-720Y	32Δ/19Y	950	-300	390	74	115
		60	17.5	380-480Δ	660-720Y	33Δ/19Y	1150	-330	370	78	
2GB 910 H07	单	50	8.5	345-415Δ	600-720Y	18.2Δ/10.5Y	1050	-190	190	74	93
		60	9.8	380-480Δ	660-720Y	18.2Δ/10.5Y	1250	-150	140	79	
2GB 910 H17	单	50	12.5	345-415Δ	600-720Y	28.0Δ/16.2Y	1050	-290	280	74	116
		60	14.5	380-480Δ	660-720Y	29.0Δ/16.7Y	1250	-270	260	79	
2GB 910 H27	单	50	15	345-415Δ	600-720Y	35.0Δ/20.0Y	1050	-320	380	74	120
		60	17.5	380-480Δ	660-720Y	36.5Δ/21.0Y	1250	-340	360	79	
2GB 910 H37	单	50	18.5	345-415Δ	600-720Y	37.0Δ/21.0Y	1050	-360	460	74	126
		60	21.3	380-480Δ	660-720Y	39.0Δ/22.5Y	1250	-380	420	79	
2GB 920 H17	双	50	12.5	345-415Δ	600-720Y	28.0Δ/16.2Y	1110	-300	270	74	187
		60	14.5	380-480Δ	660-720Y	29.0Δ/16.7Y	1310	-220	200	78	
2GB 920 H27	双	50	16.5	345-415Δ	600-720Y	35.0Δ/20.0Y	1110	-410	370	74	197
		60	19	380-480Δ	660-720Y	36.5Δ/21.0Y	1310	-340	300	78	

型号 2GB (3AC)	单叶轮	马达参数		额定电压		额定电流	最大	额定	额定	噪音 noises dB(A)	重量 Weight Kg
	双叶轮	频率	功率	电压		电流	排吸流量	真空压力	压缩压力		
	single	frequency	power	voltage		current	Max airflow	rated Vacuum	rated compress		
	double	HZ	KW	V		A	m3/h	mbar	mbar		
2GB 920 H37	双	50	20	345-415 Δ	600-720Y	40.0 Δ / 23.0Y	1110	-440	500	74	204
		60	23	380-480 Δ	660-720Y	42.0 Δ / 24.2Y	1310	-440	430	78	
2GB 920 H47	双	50	25	345-415 Δ	600-720Y	52.0 Δ / 30.0Y	1110	-440	590	74	211
		60	29	380-480 Δ	660-720Y	52.0 Δ / 30.0Y	1310	-440	540	78	
2GB 930 H07	单	50	8.5	345-415 Δ	600-720Y	18.2 Δ / 10.5Y	1370	-120	110	75	98
		60	9.8	380-480 Δ	660-720Y	18.2 Δ / 10.5Y	1650	-80	70	80	
2GB 930 H17	单	50	12.5	345-415 Δ	600-720Y	28.0 Δ / 16.2Y	1370	-190	180	75	121
		60	14.5	380-480 Δ	660-720Y	29.0 Δ / 22.5Y	1650	-150	150	80	
2GB 930 H37	单	50	18.5	345-415 Δ	600-720Y	37.0 Δ / 21.0Y	1370	-310	320	75	131
		60	21.3	380-480 Δ	660-720Y	39.0 Δ / 22.5Y	1650	-300	280	80	
2GB 940 H27	双	50	15	345-415 Δ	600-720Y	35.0 Δ / 20.0Y	1940	-130	110	75	187
		60	17.5	380-480 Δ	660-720Y	36.5 Δ / 21.0Y	2310	-60	40	84	
2GB 940 H37	双	50	20	345-415 Δ	600-720Y	40.0 Δ / 23.0Y	1940	-220	200	75	212
		60	23	380-480 Δ	660-720Y	42.0 Δ / 24.2Y	2310	-160	130	84	
2GB 940 H47	双	50	25	345-415 Δ	600-720Y	52.0 Δ / 30.0Y	1940	-310	280	75	219
		60	29	380-480 Δ	660-720Y	52.0 Δ / 30.0Y	2310	-270	220	84	
2GB 943 H27	双	50	15	345-415 Δ	600-720Y	35.0 Δ / 20.0Y	2050	-160	170	75	220
		60	17.5	380-480 Δ	660-720Y	36.5 Δ / 21.0Y	2480	-120	110	84	
2GB 943 H37	双	50	20	345-415 Δ	600-720Y	40.0 Δ / 23.0Y	2050	-250	230	75	230
		60	23	380-480 Δ	660-720Y	42.0 Δ / 24.2Y	2480	-190	180	84	
2GB 943 H47	双	50	25	345-415 Δ	600-720Y	52.0 Δ / 30.0Y	2050	-310	280	75	235
		60	29	380-480 Δ	660-720Y	52.0 Δ / 30.0Y	2480	-270	230	84	

2GB单相	单叶轮	马达额定参数				最大	额定	额定	噪音	重量
	双叶轮	频率	功率	电压	电流	排吸流量	真空压力	压缩压力		
	single double	frequency HZ	power KW	voltage V	current A	Max airflow m3/h	rated Vacuum mbar	rated compress mbar		
2GB 210 A11	单	50	0.4	220-240V	2.7	80	-120	130	53	10
		60	0.5	220-240V	3.2	98	-150	160	56	
2GB 220 A11	双	50	0.7	220-240V	4.5	88	-210	240	55	16
		60	0.83	220-240V	5.6	103	-250	250	61	
2GB 230 A11	单	50	0.4	220-240V	2.7	100	-110	110	54	11
		60	0.5	220-240V	3	120	-130	140	57	
2GB 310 A01	单	50	0.55	220-240V	3.7	95	-120	130	57	13
		60	0.62	220-240V	4.9	110	-120	130	60	
2GB 310 A11	单	50	0.7	220-240V	4.8	100	-150	150	55	14
		60	0.8	220-240V	4.1	120	-150	160	57	
2GB 320 A21	双	50	0.85	220-240V	6	120	-220	260	58	16
		60	0.95	220-240V	7.2	145	-210	240	60	
2GB 320 A31	双	50	1.3	220-240V	7.3	120	-240	280	58	17
		60	1.5	220-240V	8.3	145	-230	260	60	
2GB 330 A11	单	50	0.7	220-240V	4.8	145	-100	100	56	14
		60	0.8	220-240V	4.1	165	-110	100	58	
2GB 410 A01	单	50	0.7	220-240V	4.5	145	-120	120	63	15
		60	0.83	220-240V	5.6	175	-130	130	64	
2GB 410 A11	单	50	0.85	220-240V	5	145	-160	160	63	16
		60	0.95	220-240V	5.8	175	-160	160	64	
2GB 410 A21	单	50	1.3	220-240V	7.3	145	-170	200	63	17
		60	1.5	220-240V	7.8	175	-210	220	64	
2GB 420 A21	双	50	1.3	220-240V	7.5	150	-255	255	66	25
		60	1.5	220-240V	8	180	-290	280	69	
2GB 420 A31	双	50	1.5	220-240V	9	150	-260	260	66	28
		60	1.75	220-240V	9.5	180	-300	290	69	



2GB 单相	单叶轮	马达额定参数				最大	额定	额定	噪音	重量
	双叶轮	频率	功率	电压	电流	排吸流量	真空压力	压缩压力		
	single double	frequency HZ	power KW	voltage V	current A	Max airflow m3/h	rated Vacuum mbar	rated compress mbar		
2GB 420 A11	双	50	2.2	220-240V	10	150	-265	265	66	31
		60	2.55	220-240V	11	180	-310	300	69	
2GB 430 A11	双	50	0.85	220-240V	5.2	180	-100	110	64	16
		60	0.95	220-240V	5.8	210	-100	110	66	
2GB 430 A21	双	50	1.3	220-240V	7.3	180	-150	140	64	17
		60	1.5	220-240V	8.3	210	-140	130	66	
2GB 510 A01	单	50	0.85	220-240V	5	210	-160	160	64	20
		60	0.95	220-240V	5.8	255	-145	140	70	
2GB 510 A11	单	50	1.3	220-240V	7.3	210	-170	170	64	22
		60	1.5	220-240V	7.5	255	-150	140	70	
2GB 510 A21	单	50	1.5	220-240V	9	210	-200	190	64	24
		60	1.75	220-240V	9.5	255	-220	210	70	
2GB 510 A31	单	50	2.2	220-240V	10	210	-220	210	64	26
		60	2.55	220-240V	11	255	-240	230	70	
2GB 520 A31	双	50	2.2	220-240V	10	230	-290	360	72	38
		60	2.55	220-240V	11	275	-350	330	74	
2GB 530 A21	单	50	1.5	220-240V	10.4	270	-150	140	65	26
		60	1.75	220-240V	11.2	330	-120	110	71	
2GB 610 A11	单	50	2.2	220-240V	10	270	-230	250	64	30
		60	2.55	220-240V	11	315	-250	270	70	
2GB 710 A11	单	50	2.2	220-240V	12.8	318	-190	190	72	30
		60	2.55	220-240V	12.8	376	-190	200	74	

型号 (4GB 单相)	单叶轮	马达额定参数				最大	额定	额定	噪音	重量
	双叶轮	频率	功率	额定电压	额定电流	排吸流量	真空压力	压缩压力		
	级	Hz	KW	V	A	m <sup>3</sup> /h	mbar	mbar		
4GB 210 A75	单	50	0.55	200-240V	3.1	47	-230	290	57	18
		60	0.63	200-240V	7.1	57	-270	320	62	
4GB 220 A75	双	50	1.5	200-240V	9.7	47	-370	600	58	30
		60	1.75	200-240V	10.3	60	-420	660	62	
4GB 310 A75	单	50	0.94	200-240V	7.6	66	-250	350	57	18
		60	1.1	200-240V	9	80	-280	390	62	
4GB 320 A75	双	50	1.5	200-240V	9.7	65	-400	550	59	32
		60	1.75	200-240V	10.3	76	-390	540	53	
4GB 410 A41	单	50	1.1	200-240V	10.1	87	-300	380	55	23
		60	1.3	200-240V	10.3	105	-350	390	62	

型号 (4GBB 3AC)	单叶轮	马达额定参数				最大	额定	额定	噪音	重量
	双叶轮	频率	功率	额定电压	额定电流	排吸流量	真空压力	压缩压力		
	single	frequency	power	voltage	current	Max airflow	rated Vacuum	rated compress		
4GB 210 H16	单	50	0.55	200-240 Δ /345-415Y	2.8 Δ /1.6Y	47	-230	290	57	16
		60	0.63	220-275 Δ /380-480Y	3 Δ /1.7Y	57	-270	320	62	
4GB 310 H16	单	50	0.55	200-240 Δ /345-415Y	2.8 Δ /1.6Y	66	-250	250	57	16
		60	0.63	200-275 Δ /380-480Y	3 Δ /1.7Y	80	-260	250	62	
4GB 310 H26	单	50	0.81	200-240 Δ /345-415Y	4 Δ /2.3Y	66	-280	350	57	17
		60	0.94	220-275 Δ /380-480Y	4 Δ /2.3Y	80	-340	360	62	
4GB 410 H16	单	50	1.1	200-240 Δ /345-415Y	5.4 Δ /3.1Y	87	-300	380	58	23
		60	1.3	220-275 Δ /380-480Y	5.4 Δ /3.1Y	105	-340	370	62	
4GB 510 H16	单	50	1.6	200-240 Δ /345-415Y	7.5 Δ /4.3Y	120	-310	360	64	26
		60	2.05	220-275 Δ /380-480Y	7.6 Δ /4.4Y	145	-340	320	68	
4GB 510 H26	单	50	2.2	200-240 Δ /345-415Y	11.4 Δ /6.6Y	120	-310	470	64	29
		60	2.55	220-275 Δ /380-480Y	11.2 Δ /6.5Y	145	-360	480	68	
4GB 610 H16	单	50	2.2	200-240 Δ /345-415Y	11.4 Δ /6.6Y	165	-340	360	65	32
		60	2.55	220-275 Δ /380-480Y	11.2 Δ /6.5Y	195	-360	315	71	
4GB 610 H36	单	50	3.3	200-240 Δ /345-415Y	13 Δ /7.5Y	165	-340	480	65	35
		60	3.8	220-275 Δ /380-480Y	14.2 Δ /8.2Y	195	-380	530	71	

型号 (4GB 3AC)	单叶轮	马达额定参数				最大	额定	额定	噪音	重量
	双叶轮	频率	功率	额定电压	额定电流	排吸流量	真空压力	压缩压力		
	single	frequency	power	voltage	current	Max airflow	rated Vacuum	rated compress		
	double	HZ	KW	V	A	m <sup>3</sup> /h	mbar	mbar		
4GB 220 H26	双	50	0.81	200-240 Δ /345-415Y	4 Δ /2.3Y	47	-370	490	58	24
		60	0.94	220-275 Δ /380-480Y	4 Δ /2.3Y	60	-440	480	62	
4GB 220 H56	双	50	1.6	200-240 Δ /345-415Y	7.5 Δ /4.3Y	47	-370	650	58	28
		60	2.05	200-275 Δ /380-480Y	7.6 Δ /4.4Y	60	-500	740	62	
4GB 320 H46	双	50	1.1	200-240 Δ /345-415Y	5.4 Δ /3.1Y	65	-400	480	59	29
		60	1.3	220-275 Δ /380-480Y	5.4 Δ /3.1Y	76	-480	480	63	
4GB 320 H56	双	50	1.6	200-240 Δ /345-415Y	7.5 Δ /4.3Y	65	-440	540	59	30
		60	2.05	220-275 Δ /380-480Y	7.5 Δ /4.4Y	76	-560	600	63	
4GB 420 H26	双	50	1.6	200-240 Δ /345-415Y	7.5 Δ /4.3Y	87	-480	450	61	33
		60	2.05	220-275 Δ /380-480Y	7.6 Δ /4.4Y	105	-430	410	66	
4GB 420 H56	双	50	3.3	200-240 Δ /345-415Y	13 Δ /7.5Y	87	-500	750	61	39
		60	3.8	220-275 Δ /380-480Y	13.8 Δ /8Y	105	-510	850	66	
4GB 520 H26	双	50	2.2	200-240 Δ /345-415Y	11.4 Δ /6.6Y	120	-470	460	64	40
		60	2.55	220-275 Δ /380-480Y	11.2 Δ /6.5Y	145	-500	450	70	
4GB 520 H77	双	50	4.3	345-415 Δ	9.5 Δ	120	-500	820	65	51
		60	4.8	380-480 Δ	10 Δ	145	-530	810	71	
4GB 620 H36	双	50	3.3	200-240 Δ /345-415Y	13 Δ /7.5Y	165	-460	500	67	48
		60	3.8	220-275 Δ /380-480Y	14.2 Δ /8.2Y	195	-480	420	71	
4GB 620 H57	双	50	5.5	345-415 Δ	12 Δ	165	-460	740	68	65
		60	6.3	380-480 Δ	11.5 Δ	195	-480	840	72	
4GB 630 H67	三	50	7.5	345-415 Δ	16 Δ	170	-730	1040	72	86
		60	8.6	380-480 Δ	16 Δ	200	-700	1040	76	